

View Online at <https://aerobasegroup.com/nsn/5306-01-230-3358>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.500 inches and 0.579 inches

Eye Inside Diameter:

Between 0.250 inches and 0.253 inches

Shoulder Thickness:

Between 0.078 inches and 0.110 inches

Shank Length:

Between 0.578 inches and 0.625 inches

Eye Stock Thickness:

Between 0.183 inches and 0.193 inches

Shoulder Diameter:

Between 0.609 inches and 0.641 inches

Shank Unthreaded Hole Diameter:

0.066 inches and 0.086 inches first hole

Overall Length:

1.484 inches

Thread Diameter:

0.312 inches

Thread Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

125000 pounds per square inch

Hardness Rating:

26.0 rockwell c and 32.0 rockwell c

Distance From Center Of Eye To Shank End:

1.125 inches

Distance From Threaded End To Shank Hole Center:

0.405 inches and 0.437 inches first hole

Eye Outside Width:

Between 0.609 inches and 0.641 inches

Material:

Steel comp 431

Material Specification:

Mil-s-18732 military specification single material response

Surface Treatment:

Passivate

Style Designator:

Round, closed w/shoulder

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-18732 spec.