NSN 5306-01-231-5896

Shoulder Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-231-5896

Thread Class: За **Thread Direction:** Right-hand Thread Length: Between 0.788 inches and 0.838 inches **Fastener Length:** Between 2.110 inches and 2.140 inches **Head Style:** Double hexagon w/hole **Head Height:** Between 0.494 inches and 0.514 inches Width Between Flats: Between 0.553 inches and 0.564 inches **Extended Washer Diameter:** Between 0.818 inches and 0.828 inches **Extended Washer Thickness:** Between 0.113 inches and 0.133 inches **Shoulder Diameter:** 0.5297 inches and 0.5307 inches first shoulder **Shoulder Length:** 1.302 inches and 1.322 inches first shoulder **Thread Diameter:** 0.500 inches

Thready Qty Per Inch (tpi):

20

Min. Tensile Strength (psi):

220000 pounds per square inch

Hardness Rating:

46.0 rockwell c and 49.0 rockwell c

Shoulder Shape:

Round first shoulder

Material:

Steel comp h11

Material Specification:

Ams 6487 assn standard single material response

Surface Treatment:

Nickel and cadmium and chromate

Surface Treatment Specification:

Bps-f-69, class 220fa6 mfr ref all treatment responses

Thread Series Designator:

Unjf

NSN 5306-01-231-5896

Shoulder Bolt - Page 2 of 2



_					
•	n	0 1	•	12	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0