NSN 5306-01-231-9338

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-231-9338

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.390 inches
Fastener Length:
Between 0.625 inches and 0.655 inches
Head Style:
Double hexagon w/hole
Head Height:
Between 0.190 inches and 0.210 inches
Width Between Flats:
Between 0.243 inches and 0.251 inches
Extended Washer Diameter:
Between 0.359 inches and 0.369 inches
Extended Washer Thickness:
Between 0.040 inches and 0.060 inches
Hole Diameter:
Between 0.032 inches and 0.042 inches
Grip Diameter:
Between 0.1890 inches and 0.1895 inches
Thread Diameter:
0.190 inches
Grip Length:
Between 0.240 inches and 0.260 inches
Hole Quantity:
4
Hole Type:
Drilled
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
200000 pounds per square inch
Hole Configuration Style:
Double hexagon longitudinal hole
Material:
Iron alloy 660

Unjf

Material Specification:

Thread Series Designator:

Ams 5737 assn standard single material response

NSN 5306-01-231-9338

Shear Bolt - Page 2 of 2



_					
٠.	n	_	I+	18	e:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A003b0