

View Online at <https://aerobasegroup.com/nsn/5306-01-232-5090>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.396 inches

**Fastener Length:**

0.956 inches

**Head Style:**

Round w/wrench flats chamfered

**Head Diameter:**

Between 0.760 inches and 0.790 inches

**Head Height:**

0.250 inches

**Width Between Flats:**

0.625 inches

**Shank Unthreaded Hole Diameter:**

0.076 inches and 0.086 inches first hole

**First Diameter From Head:**

0.453 inches

**Second Diameter From Head:**

Between 0.488 inches and 0.498 inches

**Third Diameter From Head:**

Between 0.190 inches and 0.200 inches

**Distance From Largest Bearing Surface Of Head To End Of First Diameter:**

0.094 inches

**Distance From Largest Bearing Surface Of Head To End Of Second Diameter:**

0.466 inches

**Distance From Largest Bearing Surface Of Head To End Of Third Diameter:**

0.560 inches

**Thread Diameter:**

0.250 inches

**Features Provided:**

Finished head

**Thready Qty Per Inch (tpi):**

28

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

0.850 inches first hole

**Externally Relieved Body Diameter Quantity:**

2

**Material:**

Iron alloy 660

**Material Specification:**

Ams 5737 assn standard single material response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0