

View Online at <https://aerobasegroup.com/nsn/5306-01-232-5090>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.396 inches

Fastener Length:

0.956 inches

Head Style:

Round w/wrench flats chamfered

Head Diameter:

Between 0.760 inches and 0.790 inches

Head Height:

0.250 inches

Width Between Flats:

0.625 inches

Shank Unthreaded Hole Diameter:

0.076 inches and 0.086 inches first hole

First Diameter From Head:

0.453 inches

Second Diameter From Head:

Between 0.488 inches and 0.498 inches

Third Diameter From Head:

Between 0.190 inches and 0.200 inches

Distance From Largest Bearing Surface Of Head To End Of First Diameter:

0.094 inches

Distance From Largest Bearing Surface Of Head To End Of Second Diameter:

0.466 inches

Distance From Largest Bearing Surface Of Head To End Of Third Diameter:

0.560 inches

Thread Diameter:

0.250 inches

Features Provided:

Finished head

Thready Qty Per Inch (tpi):

28

Distance From Head Largest Bearing Surface To Shank Hole Center:

0.850 inches first hole

Externally Relieved Body Diameter Quantity:

2

Material:

Iron alloy 660

Material Specification:

Ams 5737 assn standard single material response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0