

View Online at <https://aerobasegroup.com/nsn/5306-01-232-9750>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

0.200 inches

**Fastener Length:**

0.750 inches

**Head Diameter:**

Between 0.153 inches and 0.157 inches

**First Diameter From Head:**

0.075 inches

**Distance From Largest Bearing Surface Of Head To End Of First Diameter:**

Between 0.438 inches and 0.442 inches

**Internal Drive Style:**

Hexagon

**Thread Diameter:**

0.112 inches

**Width Across Flats:**

0.094 inches

**Features Provided:**

Finished head

**Thready Qty Per Inch (tpi):**

40

**Min. Tensile Strength (psi):**

80000 pounds per square inch

**Minimum Yield Strength:**

30000 pounds per square inch

**Externally Relieved Body Diameter Quantity:**

1

**Surface Finish:**

32.0 microinches sides of head

**Material:**

Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316

**Material Specification:**

66 federal standard all material responses

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

**Thread Series Designator:**

Unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0