Externally Relieved Body Bolt - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5306-01-233-5070

| Thread Class    | S:  |
|-----------------|---|
| 2a              |   |
| Thread Direc    | tion:   |
| Right-hand      |   |
| Thread Leng     | th:   |
| 0.500 inches    |   |
| Fastener Len    | ngth:   |
| 1.500 inches    |   |
| Head Style:     |   |
| Dished hexag    | jon   |
| Width Betwe     | en Flats:   |
| 0.750 inches    |   |
| First Diamete   | er From Head:   |
| Between 0.37    | '0 inches and 0.380 inches  |
| Distance Fro    | m Largest Bearing Surface Of Head To End Of First Diameter:   |
| 1.000 inches    |   |
| Thread Diam     | eter:   |
| 0.500 inches    |   |
| Thready Qty     | Per Inch (tpi):   |
| 13              |   |
| Criticality Co  | ode Justification:  |
| Zzzy            |   |
| Externally Re   | elieved Body Diameter Quantity:   |
| 1               |   |
| Material:       |   |
| Stainless stee  |   |
| Thread Serie    | s Designator:   |
| Unc             |   |
| Reference N     | umber Differentiating Characteristics:  |
| Material will b | e in accordance with ships parts control center activity hx quality control, manufacturing and testing specifications |
| Shelf Life:     |   |
| N/a             |   |
| Unit Of Meas    | sure:   |
|                 |   |
| Demilitarizat   | ion:  |
| No              |   |
| Fiig:           |   |
| A003b0          |   |