

View Online at <https://aerobasegroup.com/nsn/5306-01-234-2537>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.620 inches and 0.700 inches

**Fastener Length:**

Between 0.990 inches and 1.010 inches

**Head Style:**

Double hexagon w/hole

**Head Height:**

Between 0.250 inches and 0.270 inches

**Width Between Flats:**

Between 0.243 inches and 0.251 inches

**Extended Washer Diameter:**

Between 0.365 inches and 0.385 inches

**Extended Washer Thickness:**

Between 0.040 inches and 0.050 inches

**Hole Diameter:**

0.047 inches

**Thread Diameter:**

0.190 inches

**Grip Length:**

Between 0.310 inches and 0.370 inches

**Hole Quantity:**

4

**Hole Type:**

Drilled

**Features Provided:**

Finished head

**Thready Qty Per Inch (tpi):**

32

**Hardness Rating:**

42.0 rockwell c and 46.0 rockwell c

**Hole Configuration Style:**

Double hexagon longitudinal hole

**Surface Finish:**

32.0 microinches threads

**Material:**

Steel comp 601

**Surface Treatment:**

Nickel and cadmium

**Surface Treatment Specification:**

Ams2416 assn standard single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0