

View Online at <https://aerobasegroup.com/nsn/5306-01-234-5216>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.311 inches and 0.378 inches

Fastener Length:

Between 5.478 inches and 5.498 inches

Head Style:

Hexagon

Head Height:

Between 0.296 inches and 0.328 inches

Width Between Flats:

Between 0.928 inches and 0.940 inches

Shoulder Diameter:

0.6235 inches first shoulder and 0.6240 inches first shoulder

Shoulder Length:

2.310 inches first shoulder and 2.330 inches first shoulder

Locking Feature:

Detent ring grip

Shank Unthreaded Hole Diameter:

0.076 inches first hole and 0.086 inches first hole

Thread Diameter:

0.312 inches

Thready Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

180000 pounds per square inch

Distance From Head Largest Bearing Surface To Shank Hole Center:

5.363 inches first hole and 5.393 inches first hole

Shoulder Shape:

Round first shoulder

Material:

Steel

Surface Treatment:

Passivate

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0