

View Online at <https://aerobasegroup.com/nsn/5306-01-234-9403>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.927 inches and 1.052 inches

Fastener Length:

Between 3.485 inches and 3.515 inches

Head Style:

Spline extended washer

Head Height:

Between 0.472 inches and 0.512 inches

Width Between Flats:

Between 0.222 inches and 0.227 inches

Extended Washer Diameter:

Between 1.384 inches and 1.394 inches

Extended Washer Thickness:

Between 0.098 inches and 0.118 inches

Grip Diameter:

Between 0.9980 inches and 0.9990 inches

Shank Unthreaded Hole Diameter:

0.141 inches all holes and 0.146 inches all holes

Thread Diameter:

0.750 inches

Grip Length:

Between 2.438 inches and 2.458 inches

Thready Qty Per Inch (tpi):

16

Min. Tensile Strength (psi):

220000 pounds per square inch

Distance From Head Largest Bearing Surface To Shank Hole Center:

3.267 inches all holes and 3.307 inches all holes

Special Features:

Two holes 90 degrees apart

Material:

Steel comp xm-13

Material Specification:

Ams 5629 assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0