

View Online at <https://aerobasegroup.com/nsn/5306-01-235-3164>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.606 inches and 0.673 inches

**Fastener Length:**

Between 2.366 inches and 2.413 inches

**Head Style:**

Double hexagon

**Head Height:**

Between 0.340 inches and 0.360 inches

**Width Between Flats:**

Between 0.928 inches and 0.940 inches

**Grip Diameter:**

Between 0.6230 inches and 0.6240 inches

**Shank Unthreaded Hole Diameter:**

0.131 inches first hole and 0.151 inches first hole

**Thread Diameter:**

0.625 inches

**Grip Length:**

Between 1.740 inches and 1.760 inches

**Thready Qty Per Inch (tpi):**

18

**Min. Tensile Strength (psi):**

132000 pounds per square inch

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

2.110 inches first hole and 2.142 inches first hole

**Surface Finish:**

32.0 microinches grip

**Special Features:**

Cetyl alcohol lub

**Material:**

Steel

**Material Specification:**

H-11 stsbs000 fscm 98897 mfr ref single material response

**Surface Treatment:**

Nickel and cadmium and chromate

**Surface Treatment Specification:**

Stsbs000 fsc-98897 mfr ref single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0