

View Online at <https://aerobasegroup.com/nsn/5306-01-235-3164>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.606 inches and 0.673 inches

Fastener Length:

Between 2.366 inches and 2.413 inches

Head Style:

Double hexagon

Head Height:

Between 0.340 inches and 0.360 inches

Width Between Flats:

Between 0.928 inches and 0.940 inches

Grip Diameter:

Between 0.6230 inches and 0.6240 inches

Shank Unthreaded Hole Diameter:

0.131 inches first hole and 0.151 inches first hole

Thread Diameter:

0.625 inches

Grip Length:

Between 1.740 inches and 1.760 inches

Thready Qty Per Inch (tpi):

18

Min. Tensile Strength (psi):

132000 pounds per square inch

Distance From Head Largest Bearing Surface To Shank Hole Center:

2.110 inches first hole and 2.142 inches first hole

Surface Finish:

32.0 microinches grip

Special Features:

Cetyl alcohol lub

Material:

Steel

Material Specification:

H-11 stsbs000 fscm 98897 mfr ref single material response

Surface Treatment:

Nickel and cadmium and chromate

Surface Treatment Specification:

Stsbs000 fsc-98897 mfr ref single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0