

View Online at <https://aerobasegroup.com/nsn/5306-01-236-1581>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 1.205 inches and 1.282 inches

Fastener Length:

Between 1.265 inches and 1.312 inches

Head Style:

Undercut hexagon

Head Height:

0.375 inches

Width Between Flats:

Between 0.740 inches and 0.752 inches

Hole Diameter:

Between 0.070 inches and 0.080 inches

Thread Diameter:

0.500 inches

Grip Length:

Between 0.030 inches and 0.060 inches

Hole Quantity:

3

Hole Type:

Drilled

Thready Qty Per Inch (tpi):

20

Min. Tensile Strength (psi):

160000 pounds per square inch

Hardness Rating:

36.0 rockwell c and 40.0 rockwell c

Hole Configuration Style:

Hexagon flats

Material:

Steel comp 4140 or steel comp 8740 or steel comp 8630 or steel comp 8735 or steel comp 4130 or steel comp 4037

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416 type 2 cl 2 federal specification single treatment response

Thread Series Designator:

Unjf

Specification Data:

80205-nas568 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0