NSN 5306-01-236-1581

Machine Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-236-1581

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 1.205 inches and 1.282 inches
Fastener Length:
Between 1.265 inches and 1.312 inches
Head Style:
Undercut hexagon
Head Height:
0.375 inches
Width Between Flats:
Between 0.740 inches and 0.752 inches
Hole Diameter:
Between 0.070 inches and 0.080 inches
Thread Diameter:
0.500 inches
Grip Length:
Between 0.030 inches and 0.060 inches
Hole Quantity:
3
Hole Type:
Drilled
Thready Qty Per Inch (tpi):
20
Min. Tensile Strength (psi):
160000 pounds per square inch
Hardness Rating:
36.0 rockwell c and 40.0 rockwell c
Hole Configuration Style:
Hexagon flats
Material:
Steel comp 4140 or steel comp 8740 or steel comp 8630 or steel comp 8735 or steel comp 4130 or steel comp 4037
Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:
Qq-p-416 type 2 cl 2 federal specification single treatment response
Thread Series Designator:
Unjf
Specification Data:
80205-nas568 professional/industrial association standard

NSN 5306-01-236-1581

Machine Bolt - Page 2 of 2



	L -	11		ife	_
3	ne	п	_	пe	Ξ

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0