NSN 5306-01-236-1599

Shoulder Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-236-1599

| Thread Class: |
|--|
| 2a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| Between 0.949 inches and 1.020 inches |
| Fastener Length: |
| 1.100 inches |
| Head Style: |
| Hexagon |
| Head Height: |
| 0.120 inches |
| Width Between Flats: |
| 0.500 inches |
| Shoulder Diameter: |
| 0.375 inches first shoulder |
| Shoulder Length: |
| 0.080 inches first shoulder |
| Shank Unthreaded Hole Diameter: |
| 0.078 inches first hole |
| Thread Diameter: |
| 0.250 inches |
| Thready Qty Per Inch (tpi): |
| 28 |
| Distance From Head Largest Bearing Surface To Shank Hole Center: |
| 1.010 inches first hole |
| Shoulder Shape: |
| Round first shoulder |
| Special Features: |
| Shoulder has flat to 0.342 in. |
| Material: |
| Steel comp 1018 |
| Material Specification: |
| Astm-a-108 assn standard single material response |
| Surface Treatment: |
| Cadmium and chromate |
| Surface Treatment Specification: |
| Qq-p-416, type 2 class 2 federal specification single treatment response |
| Thread Series Designator: |
| Unf |
| Shelf Life: |
| N/a |

NSN 5306-01-236-1599

Shoulder Bolt - Page 2 of 2



| | | eas | |
|--|--|-----|--|

--

Demilitarization:

No

Fiig:

A003b0