NSN 5306-01-236-1602

Shoulder Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-236-1602 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.589 inches and 0.639 inches **Fastener Length:** Between 2.474 inches and 2.504 inches **Head Style:** Double hexagon w/hole **Head Height:** Between 0.378 inches and 0.398 inches Width Between Flats: Between 0.430 inches and 0.439 inches **Extended Washer Diameter:** Between 0.369 inches and 0.649 inches **Extended Washer Thickness:** Between 0.081 inches and 0.101 inches **Shoulder Diameter:** 0.4052 inches first shoulder and 0.4057 inches first shoulder **Shoulder Length:** 1.865 inches first shoulder and 1.885 inches first shoulder **Thread Diameter:** 0.375 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 220000 pounds per square inch **Shoulder Shape:** Round first shoulder Material: Steel comp xm-13 **Material Specification:** Ams5629 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unjf Shelf Life:

N/a

NSN 5306-01-236-1602 Shoulder Bolt - Page 2 of 2



	• •				
In	18	<i>(</i>)+	МА	261	ıre:

Demilitarization:

No

Fiig:

A003b0