NSN 5306-01-236-1639

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-236-1639 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.877 inches and 0.927 inches **Fastener Length:** Between 2.012 inches and 2.042 inches **Head Style:** Dished hexagon **Head Height:** Between 0.312 inches and 0.327 inches Width Between Flats: Between 0.928 inches and 0.940 inches **Grip Diameter:** Between 0.6230 inches and 0.6240 inches **Thread Diameter:** 0.625 inches **Grip Length:** Between 1.115 inches and 1.135 inches Thready Qty Per Inch (tpi): 18 Min. Tensile Strength (psi): 160000 pounds per square inch **Surface Finish:** 32.0 microinches threads Material: Iron alloy 660 **Material Specification:** Ams5731 assn standard single material response or ams5737 assn standard single material response **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416, type 2 class 2 federal specification single treatment response **Thread Series Designator:** Unjf **Specification Data:**

Unit Of Measure:

N/a

Shelf Life:

80205-nas6710 professional/industrial association standard

NSN 5306-01-236-1639

Shear Bolt - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0