## NSN 5306-01-236-1641

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-236-1641 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.429 inches and 0.479 inches **Fastener Length:** Between 1.564 inches and 1.594 inches **Head Style:** Dished hexagon **Head Height:** Between 0.188 inches and 0.203 inches Width Between Flats: Between 0.554 inches and 0.564 inches **Grip Diameter:** Between 0.3735 inches and 0.3745 inches **Thread Diameter:** 0.375 inches **Grip Length:** Between 1.115 inches and 1.135 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 160000 pounds per square inch **Surface Finish:** 32.0 microinches threads Material: Iron alloy 660 **Material Specification:** Ams 5731 assn standard single material response or ams 5737 assn standard single material response **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416 type 2 class 2 federal specification single treatment response **Thread Series Designator:** Unjf **Specification Data:** 80205-nas6304 professional/industrial association standard Shelf Life:

N/a **Unit Of Measure:** 

## NSN 5306-01-236-1641

Shear Bolt - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0