## NSN 5306-01-236-1646

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-236-1646

| Thread Class:  |
|--|
| 3a   |
| Thread Direction:  |
| Right-hand   |
| Thread Length:   |
| Between 0.553 inches and 0.603 inches  |
| Fastener Length:   |
| Between 1.001 inches and 1.031 inches  |
| Head Style:  |
| Dished hexagon   |
| Head Height:   |
| Between 0.188 inches and 0.203 inches  |
| Width Between Flats:   |
| Between 0.553 inches and 0.564 inches  |
| Grip Diameter:   |
| Between 0.3735 inches and 0.3745 inches  |
| Thread Diameter:   |
| 0.375 inches   |
| Grip Length:   |
| Between 0.428 inches and 0.448 inches  |
| Thready Qty Per Inch (tpi):  |
| 24   |
| Min. Tensile Strength (psi):   |
| 160000 pounds per square inch  |
| Hardness Rating:   |
| 36.0 rockwell c and 40.0 rockwell c  |
| Surface Finish:  |
| 63.0 microinches grip  |
| Material:  |
| Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 8735 or steel comp 6150 |
| Surface Treatment:   |
| Cadmium and chromate   |
| Surface Treatment Specification:   |
| Qq-p-416, type 2, class 2 federal specification single treatment response                    |
| Thread Series Designator:  |
| Unjf   |
| Specification Data:  |
| 80205-nas1226 professional/industrial association standard                                   |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |

--

## NSN 5306-01-236-1646

Shear Bolt - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0