NSN 5306-01-236-4354

Externally Relieved Body Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-236-4354 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.470 inches and 0.510 inches **Fastener Length:** Between 0.580 inches and 0.600 inches **Head Style:** Hexagon **Head Height:** Between 0.205 inches and 0.215 inches Width Between Flats: Between 0.553 inches and 0.564 inches **First Diameter From Head:** Between 0.189 inches and 0.194 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.090 inches and 0.111 inches **Thread Diameter:** 0.250 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 130000 pounds per square inch Hardness Rating: 24.0 rockwell c and 35.0 rockwell c Minimum Yield Strength: 85000 pounds per square inch **Externally Relieved Body Diameter Quantity:** 1 **Special Features:** Furnished with actuation ring in head Material: Iron alloy 660 **Material Specification:** Ams 5731 assn standard single material response **Thread Series Designator:** Unjf Shelf Life: N/a **Unit Of Measure:**

--

NSN 5306-01-236-4354

Externally Relieved Body Bolt - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0