

View Online at <https://aerobasegroup.com/nsn/5306-01-236-7082>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.609 inches and 0.688 inches

**Fastener Length:**

Between 3.187 inches and 3.234 inches

**Head Style:**

Hexagon

**Head Height:**

Between 0.203 inches and 0.235 inches

**Width Between Flats:**

Between 0.553 inches and 0.565 inches

**Shank Unthreaded Hole Diameter:**

0.106 inches first hole and 0.116 inches first hole

**Thread Diameter:**

0.375 inches

**Grip Length:**

Between 2.546 inches and 2.578 inches

**Features Provided:**

Finished head

**Thready Qty Per Inch (tpi):**

24

**Min. Tensile Strength (psi):**

125000 pounds per square inch

**Hardness Rating:**

26.0 rockwell c and 32.0 rockwell c

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

2.984 inches first hole and 3.016 inches first hole

**Material:**

Steel comp 431

**Material Specification:**

Mil-s-18732 military specification single material response

**Surface Treatment:**

Passivate

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0

**Mil-std (military Standard):**

Mil-s-18732 spec.