NSN 5306-01-236-7083

Machine Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-236-7083

Thread Class: За **Thread Direction:** Right-hand Thread Length: Between 0.740 inches and 0.820 inches **Fastener Length:** Between 1.365 inches and 1.385 inches **Head Style:** Double hexagon w/hole **Head Height:** Between 0.320 inches and 0.340 inches Width Between Flats: Between 0.305 inches and 0.313 inches **Extended Washer Diameter:** Between 0.428 inches and 0.448 inches **Extended Washer Thickness:** Between 0.060 inches and 0.070 inches **Thread Diameter:** 0.250 inches **Grip Length:** Between 0.565 inches and 0.625 inches **Features Provided:** Finished head Thready Qty Per Inch (tpi): 28 Hardness Rating: 42.0 rockwell c and 46.0 rockwell c **Surface Finish:** 32.0 microinches threads Material: Steel comp 601 **Material Specification:** Ams6304 assn standard single material response **Surface Treatment:** Nickel and cadmium **Surface Treatment Specification:** Ams2416 assn standard single treatment response **Thread Series Designator:**

Unjf

Shelf Life:

N/a

NSN 5306-01-236-7083

Machine Bolt - Page 2 of 2



	• •				
In	18	<i>(</i>)+	МЛО	201	ure:

--

Demilitarization:

No

Fiig:

A003b0