

View Online at <https://aerobasegroup.com/nsn/5306-01-236-7102>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.401 inches and 0.546 inches

**Fastener Length:**

Between 4.208 inches and 4.228 inches

**Head Style:**

Dished hexagon

**Head Height:**

Between 0.251 inches and 0.266 inches

**Width Between Flats:**

Between 0.741 inches and 0.752 inches

**Locking Feature:**

Detent ring grip

**Grip Diameter:**

Between 0.4982 inches and 0.4991 inches

**Shank Unthreaded Hole Diameter:**

0.106 inches first hole and 0.116 inches first hole

**Thread Diameter:**

0.500 inches

**Grip Length:**

Between 3.562 inches and 3.578 inches

**Thready Qty Per Inch (tpi):**

20

**Min. Tensile Strength (psi):**

95000 pounds per square inch

**Hardness Rating:**

36.0 rockwell c and 41.0 rockwell c

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

4.088 inches first hole and 4.118 inches first hole

**Surface Finish:**

63.0 microinches grip

**Material:**

Steel comp e4340 or steel comp 8740 or steel comp 4140 or steel comp 4130 or steel comp 6150

**Surface Treatment:**

Cadmium and chromate

**Surface Treatment Specification:**

Qq-p-416 type 2 class 2 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0