

View Online at <https://aerobasegroup.com/nsn/5306-01-237-2790>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.887 inches and 0.937 inches

Fastener Length:

Between 5.709 inches and 5.739 inches

Head Style:

Spline extended washer

Head Height:

Between 0.462 inches and 0.482 inches

Width Between Flats:

Between 0.774 inches and 0.782 inches

Extended Washer Diameter:

Between 1.153 inches and 1.163 inches

Extended Washer Thickness:

Between 0.080 inches and 0.100 inches

Grip Diameter:

Between 0.6230 inches and 0.6240 inches

Thread Diameter:

0.625 inches

Grip Length:

Between 4.802 inches and 4.822 inches

Thready Qty Per Inch (tpi):

18

Min. Tensile Strength (psi):

220000 pounds per square inch

Special Features:

Electropolish non-bearing surface of head per ps13121 cage 76301

Material:

Steel comp xm-13

Material Specification:

Ams 5629 assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0