NSN 5306-01-237-2790



Shear Bolt - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5306-01-237-2790 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.887 inches and 0.937 inches **Fastener Length:** Between 5.709 inches and 5.739 inches **Head Style:** Spline extended washer **Head Height:** Between 0.462 inches and 0.482 inches Width Between Flats: Between 0.774 inches and 0.782 inches **Extended Washer Diameter:** Between 1.153 inches and 1.163 inches **Extended Washer Thickness:** Between 0.080 inches and 0.100 inches **Grip Diameter:** Between 0.6230 inches and 0.6240 inches **Thread Diameter:** 0.625 inches **Grip Length:** Between 4.802 inches and 4.822 inches Thready Qty Per Inch (tpi): 18 Min. Tensile Strength (psi): 220000 pounds per square inch **Special Features:** Electropolish non-bearing surface of head per ps13121 cage 76301 Material: Steel comp xm-13 **Material Specification:** Ams 5629 assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

NSN 5306-01-237-2790

Shear Bolt - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A003b0