NSN 5306-01-238-3110

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-238-3110 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.965 inches and 1.015 inches **Fastener Length:** Between 2.725 inches and 2.755 inches **Head Style:** Dished hexagon **Head Height:** Between 0.250 inches and 0.265 inches Width Between Flats: Between 0.741 inches and 0.752 inches **Grip Diameter:** Between 0.4988 inches and 0.4995 inches **Thread Diameter:** 0.500 inches **Grip Length:** Between 1.740 inches and 1.760 inches Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 34.0 rockwell c and 40.0 rockwell c **Special Features:** Retaining element in extended dia. Of threaded end Material: Steel comp e4340 or steel comp 4140 or steel comp 8735 or steel comp 6150 **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416 ty2 cl3 federal specification single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a **Unit Of Measure:**

Demilitarization:

No

NSN 5306-01-238-3110

Shear Bolt - Page 2 of 2



Fiig:

A003b0