## NSN 5306-01-239-0582

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-239-0582 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.742 inches and 0.792 inches **Fastener Length:** Between 2.002 inches and 2.032 inches **Head Style:** Spline extended washer **Head Height:** Between 0.440 inches and 0.460 inches Width Between Flats: Between 0.547 inches and 0.562 inches **Extended Washer Diameter:** Between 0.922 inches and 0.932 inches **Extended Washer Thickness:** Between 0.062 inches and 0.082 inches **Grip Diameter:** Between 0.4990 inches and 0.4995 inches **Thread Diameter:** 0.500 inches **Grip Length:** Between 1.240 inches and 1.260 inches Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 220000 pounds per square inch Material: Steel comp xm-13 **Material Specification:** Ams5629 assn standard single material response **Surface Treatment: Passivate Thread Series Designator:** Unjf Shelf Life: N/a **Unit Of Measure:** 

**Demilitarization:**No

## NSN 5306-01-239-0582

Shear Bolt - Page 2 of 2



Fiig:

A003b0