## NSN 5306-01-241-1510

Machine Bolt - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5306-01-241-1510



**Thread Class:** 3a **Thread Direction: Right-hand Thread Length:** Between 1.218 inches and 1.297 inches Fastener Length: Between 4.172 inches and 4.219 inches **Head Style:** Hexagon **Head Height:** Between 0.453 inches and 0.485 inches Width Between Flats: Between 1.240 inches and 1.253 inches Hole Diameter: Between 0.070 inches and 0.080 inches **Thread Diameter:** 0.875 inches Grip Length: Between 2.922 inches and 2.954 inches **Hole Quantity:** 1 Hole Type: Drilled **Features Provided:** Finished head Thready Qty Per Inch (tpi): 14 Min. Tensile Strength (psi): 125000 pounds per square inch Hardness Rating: 26.0 rockwell c and 32.0 rockwell c Hole Configuration Style: Hexagon flats Material: Steel comp 431 **Material Specification:** Mil-s-18732 military specification single material response Surface Treatment: Passivate **Surface Treatment Specification:** 

Qq-p-35 federal specification single treatment response

## NSN 5306-01-241-1510

Machine Bolt - Page 2 of 2

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-18732 spec.

