NSN 5306-01-241-2619

Machine Bolt - Page 1 of 2

Thread Class:

View Online at https://aerobasegroup.com/nsn/5306-01-241-2619



3a **Thread Direction: Right-hand Thread Length:** Between 0.620 inches and 0.700 inches Fastener Length: Between 1.552 inches and 1.572 inches Head Style: Double hexagon w/hole **Head Height:** Between 0.250 inches and 0.270 inches Width Between Flats: 0.250 inches **Extended Washer Diameter:** Between 0.365 inches and 0.385 inches **Extended Washer Thickness:** 0.040 inches Hole Diameter: Between 0.037 inches and 0.057 inches **Thread Diameter:** 0.190 inches Grip Length: Between 0.872 inches and 0.932 inches **Hole Quantity:** 4 Hole Type: Drilled **Features Provided:** Finished head Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 130000 pounds per square inch Hardness Rating: 24.0 rockwell c and 35.0 rockwell c **Minimum Yield Strength:** 85000 pounds per square inch Hole Configuration Style: Double hexagon longitudinal hole Surface Finish:

32.0 microinches threads

NSN 5306-01-241-2619

Machine Bolt - Page 2 of 2



Material:

Iron alloy 660

Material Specification:

Ams5731 assn standard single material response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0