NSN 5306-01-241-2643

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-241-2643

Thread Direction: Right-hand Thread Length: Between 0.413 inches and 0.463 inches Fastener Length: Between 0.735 inches and 0.765 inches Head Style: Dished hexagon Head Height: Between 0.156 inches and 0.171 inches Wildth Between 0.156 inches and 0.171 inches Wildth Between 1.156 inches and 0.502 inches Grip Diameter: Between 0.3115 inches and 0.3120 inches Grip Diameter: Between 0.3115 inches and 0.3120 inches Thread Diameter: 0.312 inches Grip Length: Between 0.302 inches and 0.322 inches Thready Oty Per Inch (tpi): 24 Min. Tensile Strength (psi): 100000 pounds per square inch Surface Finish: 32.0 microinches threads Material: Iron alloy 660 Material Specification: Ams5731 assn standard single material response or ams 5737 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: Qu-p-35 federal specification single treatment response Thread Series Designator: Unif Specification Data: 80205-nas6305 government specification Shelf Lifte: N/a Unit Of Measure:	
Thread Direction: Right-hand Thread Length: Between 0.413 inches and 0.463 inches Fastener Length: Between 0.735 inches and 0.765 inches Head Style: Dished hexagon Head Height: Between 0.156 inches and 0.171 inches Width Between 0.156 inches and 0.171 inches Width Between 1.565 inches and 0.502 inches Grip Diameter: Between 0.3115 inches and 0.3120 inches Grip Diameter: 0.312 inches Grip Length: Between 0.301 inches and 0.3120 inches Thread Diameter: 0.312 inches Grip Length: Between 0.302 inches and 0.322 inches Thready Oty Per Inch (tpi): 24 Min. Tensile Strength (psi): 160000 pounds per square inch Surface Finish: 32.0 microinches threads Material: Iron alloy 660 Material Specification: Ams5731 assn standard single material response or ams 5737 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: Oq-p-35 federal specification: Injf Specification Data: 80205-nas6305 government specification Shelf Life: N/a	Thread Class:
Right-hand Thread Length: Between 0.413 inches and 0.463 inches Fastener Length: Between 0.735 inches and 0.765 inches Head Style: Dished hexagon Head Height: Between 0.156 inches and 0.171 inches Width Between 0.156 inches and 0.171 inches Width Between 0.492 inches and 0.502 inches Grip Diameter: Between 0.3915 inches and 0.3120 inches Thread Diameter: 0.312 inches Grip Length: Between 0.302 inches and 0.322 inches Thread Oyl Per Inch (tpi): 24 Min. Tensile Strength (psi): 160000 pounds per square inch Surface Finish: 32.0 microinches threads Material: Iron alloy 660 Material Specification: Ams5731 assn standard single material response or ams 5737 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: Qq-p-36 federal specification single treatment response Thread Series Designator: Unif Specification Data: 80205-nas6305 government specification Shelf Life: N/a	3a
Thread Length: Between 0.413 inches and 0.463 inches Fastener Length: Between 0.735 inches and 0.765 inches Head Style: Dished hexagon Head Height: Between 0.156 inches and 0.171 inches Width Between Flats: Between 0.492 inches and 0.502 inches Grip Diameter: Between 0.492 inches and 0.502 inches Grip Diameter: Between 0.3115 inches and 0.3120 inches Thread Diameter: 0.312 inches Grip Length: Between 0.321 inches and 0.322 inches Thread yty Per Inch (tpi): 24 Min. Tensile Strength (psi): 160000 pounds per square inch Surface Finish: 32.0 microinches threads Material: Iron alloy 660 Material Specification: Ams5731 assn standard single material response or ams 5737 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification: Innead Series Designator: Unif Specification Data: 80205-nas6305 government specification Shelf Life: N/a	Thread Direction:
Between 0.413 inches and 0.463 inches Fastener Length: Between 0.735 inches and 0.765 inches Head Style: Dished hexagon Head Height: Between 0.156 inches and 0.171 inches Width Between Flats: Between 0.492 inches and 0.502 inches Grip Diameter: Between 0.492 inches and 0.502 inches Grip Diameter: Between 0.3115 inches and 0.3120 inches Thread Diameter: 0.312 inches Grip Length: Between 0.302 inches and 0.322 inches Thread Ojameter: 0.312 inches Grip Length: Between 0.302 inches and 0.322 inches Thread Ojameter: 0.312 inches Grip Length: Between 0.302 inches and 0.322 inches Thread Grip Length: Between 0.302 inches and 0.322 inches Thread Grip Length: Between 0.302 inches and 0.322 inches Thread Grip Length: Between 0.302 inches and 0.322 inches Thread Grip Length: Between 0.302 inches and 0.322 inches Thread Grip Length: Between 0.302 inches and 0.322 inches Thread Grip Length: Between 0.302 inches and 0.322 inches Thread Grip Length: Between 0.302 inches and 0.322 inches Thread Grip Length: Between 0.302 inches and 0.322 inches Thread Grip Length: Between 0.315 inches Grip Length: Between 0.492 inches Grip Len	Right-hand
Fastener Length: Between 0.735 inches and 0.765 inches Head Style: Dished hexagon Head Height: Between 0.156 inches and 0.171 inches Width Between Flats: Between 0.492 inches and 0.502 inches Grip Diameter: Between 0.491 inches and 0.502 inches Grip Diameter: Between 0.315 inches and 0.3120 inches Thread Diameter: 0.312 inches Grip Length: Between 0.302 inches and 0.322 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 180000 pounds per square inch Surface Finish: 32.0 microinches threads Material: Iron alloy 660 Material Specification: Ams5731 assn standard single material response or ams 5737 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator: Unif Specification Data: 80205-nas6305 government specification Shelf Life: N/a	Thread Length:
Between 0.735 inches and 0.765 inches Head Style: Dished hexagon Head Height: Between 0.156 inches and 0.171 inches Width Between Flats: Between 0.492 inches and 0.502 inches Grip Diameter: Between 0.3115 inches and 0.3120 inches Thread Diameter: 0.312 inches Grip Length: Between 0.302 inches and 0.322 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 160000 pounds per square inch Surface Finish: 32.0 microinches threads Material: Iron alloy 660 Material Specification: Ams5731 assn standard single material response or ams 5737 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator: Unif Specification Data: 80205-nas6305 government specification Shelf Life: N/a	Between 0.413 inches and 0.463 inches
Head Style: Dished hexagon Head Height: Between 0.156 inches and 0.171 inches Width Between Flats: Between 0.492 inches and 0.502 inches Grip Diameter: Between 0.3115 inches and 0.3120 inches Thread Diameter: 0.312 inches Grip Length: Between 0.302 inches and 0.322 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 160000 pounds per square inch Surface Finish: 32.0 microinches threads Material: Iron alloy 660 Material Specification: Arms5731 assn standard single material response or ams 5737 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator: Unif Specification Data: 80205-nas6305 government specification Shelf Life: N/a	Fastener Length:
Dished hexagon Head Height: Between 0.156 inches and 0.171 inches Width Between Flats: Between 0.492 inches and 0.502 inches Grip Diameter: Between 0.315 inches and 0.3120 inches Thread Diameter: 0.312 inches Grip Length: Between 0.302 inches and 0.322 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 160000 pounds per square inch Surface Finish: 32.0 microinches threads Material: Iron alloy 660 Material Specification: Ams5731 assn standard single material response or ams 5737 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator: Unif Specification Data: 80205-nas6305 government specification Shelf Life: N/a	Between 0.735 inches and 0.765 inches
Head Height: Between 0.156 inches and 0.171 inches Width Between Flats: Between 0.492 inches and 0.502 inches Grip Diameter: Between 0.3115 inches and 0.3120 inches Thread Diameter: 0.312 inches Grip Length: Between 0.302 inches and 0.322 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 160000 pounds per square inch Surface Finish: 32.0 microinches threads Material: Iron alloy 660 Material Specification: Ams5731 assn standard single material response or ams 5737 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator: Unif Specification Data: 80205-nas6305 government specification Shelf Life: N/a	Head Style:
Between 0.156 inches and 0.171 inches Width Between Flats: Between 0.492 inches and 0.502 inches Grip Diameter: Between 0.3115 inches and 0.3120 inches Thread Diameter: 0.312 inches Grip Length: Between 0.302 inches and 0.322 inches Thready Qty Per Inch (tpl): 24 Min. Tensile Strength (psi): 160000 pounds per square inch Surface Finish: 32.0 microinches threads Material: Iron alloy 660 Material Specification: Ams5731 assn standard single material response or ams 5737 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator: Unif Specification Data: 80205-nas6305 government specification Shelf Life: N/a	Dished hexagon
Width Between Flats: Between 0.492 inches and 0.502 inches Grip Diameter: Between 0.3115 inches and 0.3120 inches Thread Diameter: 0.312 inches Grip Length: Between 0.302 inches and 0.322 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 160000 pounds per square inch Surface Finish: 32.0 microinches threads Material: Iron alloy 660 Material Specification: Ams5731 assn standard single material response or ams 5737 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator: Unif Specification Data: 80205-nas6305 government specification Shelf Life: N/a	Head Height:
Between 0.492 inches and 0.502 inches Grip Diameter: Between 0.3115 inches and 0.3120 inches Thread Diameter: 0.312 inches Grip Length: Between 0.302 inches and 0.322 inches Thready Oty Per Inch (tpi): 24 Min. Tensile Strength (psi): 160000 pounds per square inch Surface Finish: 32.0 microinches threads Material: Iron alloy 660 Material Specification: Ams5731 assn standard single material response or ams 5737 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator: Unjf Specification Data: 80205-nas6305 government specification Shelf Life: N/a	Between 0.156 inches and 0.171 inches
Grip Diameter: Between 0.3115 inches and 0.3120 inches Thread Diameter: 0.312 inches Grip Length: Between 0.302 inches and 0.322 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 160000 pounds per square inch Surface Finish: 32.0 microinches threads Material: Iron alloy 660 Material Specification: Arms5731 assn standard single material response or ams 5737 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator: Unif Specification Data: 80205-nas6305 government specification Shelf Life: N/a	Width Between Flats:
Between 0.3115 inches and 0.3120 inches Thread Diameter: 0.312 inches Grip Length: Between 0.302 inches and 0.322 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 160000 pounds per square inch Surface Finish: 32.0 microinches threads Material: Iron alloy 660 Material Specification: Ams5731 assn standard single material response or ams 5737 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator: Unif Specification Data: 80205-nas6305 government specification Shelf Life: N/a	Between 0.492 inches and 0.502 inches
Thread Diameter: 0.312 inches Grip Length: Between 0.302 inches and 0.322 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 160000 pounds per square inch Surface Finish: 32.0 microinches threads Material: Iron alloy 660 Material Specification: Ams5731 assn standard single material response or ams 5737 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator: Unjf Specification Data: 80205-nas6305 government specification Shelf Life: N/a	Grip Diameter:
0.312 inches Grip Length: Between 0.302 inches and 0.322 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 160000 pounds per square inch Surface Finish: 32.0 microinches threads Material: Iron alloy 660 Material Specification: Ams5731 assn standard single material response or ams 5737 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator: Unjf Specification Data: 80205-nas6305 government specification Shelf Life: N/a	Between 0.3115 inches and 0.3120 inches
Grip Length: Between 0.302 inches and 0.322 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 160000 pounds per square inch Surface Finish: 32.0 microinches threads Material: Iron alloy 660 Material Specification: Ams5731 assn standard single material response or ams 5737 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator: Unjf Specification Data: 80205-nas6305 government specification Shelf Life: N/a	Thread Diameter:
Between 0.302 inches and 0.322 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 160000 pounds per square inch Surface Finish: 32.0 microinches threads Material: Iron alloy 660 Material Specification: Ams5731 assn standard single material response or ams 5737 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator: Unjf Specification Data: 80205-nas6305 government specification Shelf Life: N/a	0.312 inches
Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 160000 pounds per square inch Surface Finish: 32.0 microinches threads Material: Iron alloy 660 Material Specification: Ams5731 assn standard single material response or ams 5737 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator: Unjf Specification Data: 80205-nas6305 government specification Shelf Life: N/a	Grip Length:
Min. Tensile Strength (psi): 160000 pounds per square inch Surface Finish: 32.0 microinches threads Material: Iron alloy 660 Material Specification: Ams5731 assn standard single material response or ams 5737 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator: Unjf Specification Data: 80205-nas6305 government specification Shelf Life: N/a	Between 0.302 inches and 0.322 inches
Min. Tensile Strength (psi): 160000 pounds per square inch Surface Finish: 32.0 microinches threads Material: Iron alloy 660 Material Specification: Ams5731 assn standard single material response or ams 5737 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator: Unjf Specification Data: 80205-nas6305 government specification Shelf Life: N/a	Thready Qty Per Inch (tpi):
160000 pounds per square inch Surface Finish: 32.0 microinches threads Material: Iron alloy 660 Material Specification: Ams5731 assn standard single material response or ams 5737 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator: Unjf Specification Data: 80205-nas6305 government specification Shelf Life: N/a	24
Surface Finish: 32.0 microinches threads Material: Iron alloy 660 Material Specification: Ams5731 assn standard single material response or ams 5737 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator: Unjf Specification Data: 80205-nas6305 government specification Shelf Life: N/a	Min. Tensile Strength (psi):
32.0 microinches threads Material: Iron alloy 660 Material Specification: Ams5731 assn standard single material response or ams 5737 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator: Unjf Specification Data: 80205-nas6305 government specification Shelf Life: N/a	160000 pounds per square inch
Material: Iron alloy 660 Material Specification: Ams5731 assn standard single material response or ams 5737 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator: Unjf Specification Data: 80205-nas6305 government specification Shelf Life: N/a	Surface Finish:
Iron alloy 660 Material Specification: Ams5731 assn standard single material response or ams 5737 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator: Unjf Specification Data: 80205-nas6305 government specification Shelf Life: N/a	32.0 microinches threads
Material Specification: Ams5731 assn standard single material response or ams 5737 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator: Unjf Specification Data: 80205-nas6305 government specification Shelf Life: N/a	Material:
Ams5731 assn standard single material response or ams 5737 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator: Unjf Specification Data: 80205-nas6305 government specification Shelf Life: N/a	Iron alloy 660
Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator: Unjf Specification Data: 80205-nas6305 government specification Shelf Life: N/a	Material Specification:
Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator: Unjf Specification Data: 80205-nas6305 government specification Shelf Life: N/a	Ams5731 assn standard single material response or ams 5737 assn standard single material response
Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator: Unjf Specification Data: 80205-nas6305 government specification Shelf Life: N/a	Surface Treatment:
Qq-p-35 federal specification single treatment response Thread Series Designator: Unjf Specification Data: 80205-nas6305 government specification Shelf Life: N/a	Passivate
Thread Series Designator: Unjf Specification Data: 80205-nas6305 government specification Shelf Life: N/a	Surface Treatment Specification:
Unjf Specification Data: 80205-nas6305 government specification Shelf Life: N/a	Qq-p-35 federal specification single treatment response
Specification Data: 80205-nas6305 government specification Shelf Life: N/a	Thread Series Designator:
80205-nas6305 government specification Shelf Life: N/a	Unjf
Shelf Life: N/a	Specification Data:
N/a	80205-nas6305 government specification
	Shelf Life:
Unit Of Measure:	N/a
	Unit Of Measure:

--

NSN 5306-01-241-2643

Shear Bolt - Page 2 of 2



em			

No

Fiig:

A003b0