

View Online at <https://aerobasegroup.com/nsn/5306-01-241-3910>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.677 inches and 0.727 inches

Fastener Length:

Between 1.812 inches and 1.842 inches

Head Style:

Double hexagon extended washer

Head Height:

Between 0.378 inches and 0.398 inches

Width Between Flats:

0.438 inches

Extended Washer Diameter:

Between 0.639 inches and 0.649 inches

Extended Washer Thickness:

Between 0.081 inches and 0.101 inches

Grip Diameter:

Between 0.3734 inches and 0.3745 inches

Thread Diameter:

0.375 inches

Grip Length:

Between 1.115 inches and 1.135 inches

Thready Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

180000 pounds per square inch

Hardness Rating:

39.0 rockwell c and 43.0 rockwell c

Surface Finish:

32.0 microinches grip

Material:

Steel comp 4340

Material Specification:

Mil-s-8844 cl 1 military specification single material response

Surface Treatment:

Cadmium and cadmium and chromate

Surface Treatment Specification:

Ams 24901-3 assn standard 1st treatment response and qq-p-416 type 2 assn standard 2nd treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-8844 spec.