

View Online at <https://aerobasegroup.com/nsn/5306-01-241-3910>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.677 inches and 0.727 inches

**Fastener Length:**

Between 1.812 inches and 1.842 inches

**Head Style:**

Double hexagon extended washer

**Head Height:**

Between 0.378 inches and 0.398 inches

**Width Between Flats:**

0.438 inches

**Extended Washer Diameter:**

Between 0.639 inches and 0.649 inches

**Extended Washer Thickness:**

Between 0.081 inches and 0.101 inches

**Grip Diameter:**

Between 0.3734 inches and 0.3745 inches

**Thread Diameter:**

0.375 inches

**Grip Length:**

Between 1.115 inches and 1.135 inches

**Thready Qty Per Inch (tpi):**

24

**Min. Tensile Strength (psi):**

180000 pounds per square inch

**Hardness Rating:**

39.0 rockwell c and 43.0 rockwell c

**Surface Finish:**

32.0 microinches grip

**Material:**

Steel comp 4340

**Material Specification:**

Mil-s-8844 cl 1 military specification single material response

**Surface Treatment:**

Cadmium and cadmium and chromate

**Surface Treatment Specification:**

Ams 24901-3 assn standard 1st treatment response and qq-p-416 type 2 assn standard 2nd treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-s-8844 spec.