NSN 5306-01-241-6274

Machine Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-241-6274 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.624 inches and 0.703 inches **Fastener Length:** Between 4.078 inches and 4.125 inches **Head Style:** Hexagon **Head Height:** Between 0.234 inches and 0.266 inches Width Between Flats: Between 0.615 inches and 0.627 inches **Hole Diameter:** Between 0.070 inches and 0.080 inches **Thread Diameter:** 0.438 inches **Grip Length:** Between 3.422 inches and 3.454 inches **Hole Quantity:** 1 **Hole Type:** Drilled **Features Provided:** Finished head Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 125000 pounds per square inch Hardness Rating: 26.0 rockwell c and 32.0 rockwell c Material: Steel comp 431 **Material Specification:** Mil-s-18732 military specification single material response **Surface Treatment: Passivate Thread Series Designator:** Unf

Shelf Life:

N/a

NSN 5306-01-241-6274

Machine Bolt - Page 2 of 2



U	n	it	Of	Μe	eas	ur	e:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-18732 spec.