NSN 5306-01-242-1785

Close Tolerance Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-242-1785 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.282 inches and 0.333 inches **Fastener Length:** Between 1.356 inches and 1.376 inches **Head Style:** Dished hexagon **Head Height:** Between 0.126 inches and 0.141 inches Width Between Flats: Between 0.430 inches and 0.439 inches **Grip Diameter:** Between 0.2483 inches and 0.2492 inches **Thread Diameter:** 0.250 inches **Grip Length:** Between 0.938 inches and 0.954 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 95000 pounds per square inch Hardness Rating: 36.0 rockwell c and 41.0 rockwell c **Surface Finish:** 63.0 microinches grip **Special Features:** Retaining element on shank Material: Steel comp 630 **Material Specification:** Ams 5643 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:**

Unjf

Shelf Life:

N/a

NSN 5306-01-242-1785

Close Tolerance Bolt - Page 2 of 2



ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A003b0