

View Online at <https://aerobasegroup.com/nsn/5306-01-243-9412>

Thread Direction:

Right-hand

Thread Length:

Between 16.0 millimeters and 17.0 millimeters

Fastener Length:

Between 22.20 millimeters and 22.80 millimeters

Head Style:

Spline extended washer

Head Height:

Between 8.5 millimeters and 9.0 millimeters

Extended Washer Diameter:

14.8 millimeters

Extended Washer Thickness:

Between 2.1 millimeters and 2.4 millimeters

Hole Diameter:

Between 1.40 millimeters and 1.54 millimeters

Grip Diameter:

Between 7.9620 millimeters and 7.9870 millimeters

Thread Diameter:

8.0 millimeters

Grip Length:

Between 5.80 millimeters and 6.20 millimeters

Hole Quantity:

4

Hole Type:

Drilled

Min. Tensile Strength (psi):

1250 megapascals

Hardness Rating:

39.0 rockwell c and 43.0 rockwell c

Thread Pitch In Millimeters:

1.0

External Thread Tolerance Class:

4h6h

Hole Configuration Style:

Round longitudinal hole

Material:

Steel comp e4340 or steel comp 8740

Material Specification:

Mil-s-5000 military specification 1st material response or mil-s-6049 military specification 2nd material response

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416 type 2 class 2 federal specification single treatment response

Thread Series Designator:

Mj

Specification Data:

80205-na0058 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5000 spec.