## NSN 5306-01-244-1050

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-244-1050 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.490 inches and 0.540 inches **Fastener Length:** Between 1.687 inches and 1.717 inches **Head Style:** Double hexagon extended washer **Head Height:** Between 0.290 inches and 0.310 inches Width Between Flats: Between 0.306 inches and 0.315 inches **Extended Washer Diameter:** Between 0.428 inches and 0.438 inches **Extended Washer Thickness:** Between 0.059 inches and 0.079 inches **Grip Diameter:** Between 0.2485 inches and 0.2495 inches **Thread Diameter:** 0.250 inches **Grip Length:** Between 1.177 inches and 1.197 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 180000 pounds per square inch **Hardness Rating:** 39.0 rockwell c and 43.0 rockwell c Material: Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 8735 **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416, type 2 federal specification single treatment response **Thread Series Designator:** Unjf **Specification Data:** 80205-nas624 professional/industrial association standard Shelf Life:

N/a

## NSN 5306-01-244-1050

Shear Bolt - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A003b0