## NSN 5306-01-244-5250

Shoulder Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-244-5250

**Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.413 inches and 0.463 inches **Fastener Length:** Between 0.548 inches and 0.578 inches **Head Style:** Dished hexagon **Head Height:** Between 0.156 inches and 0.171 inches Width Between Flats: Between 0.492 inches and 0.502 inches **Shoulder Diameter:** 0.326 inches first shoulder and 0.327 inches first shoulder **Shoulder Length:** 0.548 inches first shoulder and 0.578 inches first shoulder **Thread Diameter:** 0.312 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 36.0 rockwell c and 40.0 rockwell c **Shoulder Shape:** Round first shoulder Material: Steel comp e4340 or steel comp 8740 **Material Specification:** Nas4002 assn standard single material response **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416, type 2, class 2 assn standard single treatment response **Thread Series Designator:** Unjf **Specification Data:** 80205-nas6205 professional/industrial association standard Shelf Life:

N/a

## NSN 5306-01-244-5250

Shoulder Bolt - Page 2 of 2



|  | Of |  |  |  |
|--|----|--|--|--|

--

Demilitarization:

No

Fiig:

A003b0