NSN 5306-01-244-8872

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-244-8872

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.531 inches and 0.581 inches
Fastener Length:
Between 1.291 inches and 1.321 inches
Head Style:
Spline extended washer
Head Height:
Between 0.302 inches and 0.322 inches
Width Between Flats:
Between 0.383 inches and 0.389 inches
Extended Washer Diameter:
Between 0.575 inches and 0.585 inches
Extended Washer Thickness:
Between 0.035 inches and 0.065 inches
Grip Diameter:
Between 0.3110 inches and 0.3120 inches
End Application:
Spec item
Thread Diameter:
0.312 inches
Grip Length:
Between 0.740 inches and 0.760 inches
Thready Qty Per Inch (tpi):
24
Min. Tensile Strength (psi):
180000 pounds per square inch
Hardness Rating:
39.0 rockwell c and 43.0 rockwell c
Surface Finish:
32.0 microinches grip
Material:
Steel comp 4140 or steel comp e4340 or steel comp 8740 or steel comp 6150
Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:
Qq-416 type 2 cl 2 federal specification single treatment response
Thread Series Designator:
Unjf

NSN 5306-01-244-8872

Shear Bolt - Page 2 of 2



-				
٠.	hΔ	Iŧ.	ife:	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0