

View Online at <https://aerobasegroup.com/nsn/5306-01-245-3826>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.710 inches and 1.150 inches

**Fastener Length:**

Between 1.210 inches and 1.250 inches

**Head Style:**

Distorted head

**Head Height:**

Between 0.125 inches and 0.135 inches

**Width Between Flats:**

Between 0.489 inches and 0.500 inches

**Locking Feature:**

Distortions top of head

**End Application:**

Spec item

**Thread Diameter:**

0.250 inches

**Grip Length:**

Between 0.100 inches and 0.500 inches

**Features Provided:**

Finished head

**Thready Qty Per Inch (tpi):**

28

**Min. Tensile Strength (psi):**

150000 pounds per square inch

**Hardness Rating:**

32.0 rockwell c and 38.0 rockwell c

**Material:**

Steel

**Material Specification:**

Sae gr 8 assn standard all material responses

**Surface Treatment:**

Cadmium and chromate

**Surface Treatment Specification:**

Qq-p-416 type 2 cl 2 federal specification single treatment response

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0