## NSN 5306-01-249-2208

Shoulder Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-249-2208 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.765 inches **Fastener Length:** 1.938 inches **Head Style:** Hexagon **Head Height:** Between 0.312 inches and 0.344 inches Width Between Flats: 0.625 inches **Shoulder Diameter:** 0.4345 inches first shoulder and 0.4355 inches first shoulder **Shoulder Length:** 1.257 inches first shoulder **Thread Diameter:** 0.375 inches Thready Qty Per Inch (tpi): 24 Hardness Rating: 32.0 rockwell c and 38.0 rockwell c **Shoulder Shape:** Round first shoulder Material: Steel comp 4135h or steel comp 5140h or steel comp 8637h **Material Specification:** Astm a304 national specification single material response **Surface Treatment:** Zinc **Surface Treatment Specification:** Qq-z-325 type 2, cl3 federal specification single treatment response

**Thread Series Designator:** Unf Shelf Life: N/a **Unit Of Measure: Demilitarization:** No

## **NSN 5306-01-249-2208** Shoulder Bolt - Page 2 of 2



Fiig:

A003b0