NSN 5306-01-249-4170

Internally Relieved Body Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-249-4170

| Threads Per Inch: |
|--|
| 28 counterbore |
| Thread Class: |
| 3a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| Between 0.460 inches and 0.510 inches |
| Fastener Length: |
| Between 0.970 inches and 1.000 inches |
| Head Style: |
| Double hexagon w/hole |
| Head Height: |
| Between 0.290 inches and 0.310 inches |
| Width Between Flats: |
| Between 0.306 inches and 0.315 inches |
| Extended Washer Diameter: |
| Between 0.428 inches and 0.438 inches |
| Extended Washer Thickness: |
| Between 0.059 inches and 0.079 inches |
| Concentric Hole Diameter: |
| 0.213 inches |
| Internal Thread Length: |
| 0.195 inches counterbore and 0.205 inches counterbore |
| Thread Diameter: |
| 0.250 inches |
| Thread Series: |
| Unf counterbore |
| Thready Qty Per Inch (tpi): |
| 28 |
| Thread Size: |
| 0.250 inches counterbore |
| Internal Thread Class: |
| 3b counterbore |
| Material: |
| Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 8735 or steel comp 6150 |
| Surface Treatment: |
| Cadmium and chromate |
| Surface Treatment Specification: |
| Qq-p-416 type 2 cl 3 federal specification single treatment response |
| Style Designator: |
| Counterbore threaded |

NSN 5306-01-249-4170

Internally Relieved Body Bolt - Page 2 of 2



| Thread Series Designator: |
|---------------------------|
| Unf |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |

A003b0