

View Online at <https://aerobasegroup.com/nsn/5306-01-249-4177>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.443 inches and 0.493 inches

**Fastener Length:**

Between 1.765 inches and 1.795 inches

**Head Style:**

Spline extended washer

**Head Height:**

Between 0.204 inches and 0.224 inches

**Width Between Flats:**

Between 0.297 inches and 0.312 inches

**Extended Washer Diameter:**

Between 0.460 inches and 0.470 inches

**Extended Washer Thickness:**

Between 0.026 inches and 0.046 inches

**Hole Diameter:**

Between 0.032 inches and 0.042 inches

**Grip Diameter:**

Between 0.2490 inches and 0.2495 inches

**Thread Diameter:**

0.250 inches

**Grip Length:**

Between 1.302 inches and 1.322 inches

**Hole Quantity:**

4

**Hole Type:**

Drilled

**Thready Qty Per Inch (tpi):**

28

**Min. Tensile Strength (psi):**

220000 pounds per square inch

**Hole Configuration Style:**

Spline

**Material:**

Steel comp xm-13

**Material Specification:**

Ams5629 assn standard single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0