

View Online at <https://aerobasegroup.com/nsn/5306-01-250-4641>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.680 inches and 0.730 inches

**Fastener Length:**

Between 1.877 inches and 1.907 inches

**Head Style:**

Spline extended washer

**Head Height:**

Between 0.320 inches and 0.340 inches

**Width Between Flats:**

Between 0.485 inches and 0.500 inches

**Extended Washer Diameter:**

Between 0.807 inches and 0.817 inches

**Extended Washer Thickness:**

Between 0.053 inches and 0.073 inches

**Hole Diameter:**

Between 0.050 inches and 0.060 inches

**Grip Diameter:**

Between 0.4365 inches and 0.4370 inches

**Thread Diameter:**

0.437 inches

**Grip Length:**

Between 1.177 inches and 1.197 inches

**Hole Quantity:**

4

**Hole Type:**

Drilled

**Thready Qty Per Inch (tpi):**

20

**Min. Tensile Strength (psi):**

220000 pounds per square inch

**Hole Configuration Style:**

Spline

**Material:**

Steel comp xm-13

**Material Specification:**

Ams5629 assn standard single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0