NSN 5306-01-250-9658

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-250-9658

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.710 inches and 0.760 inches
Fastener Length:
Between 5.095 inches and 5.125 inches
Head Style:
Dished hexagon
Head Height:
Between 0.235 inches and 0.265 inches
Width Between Flats:
Between 0.741 inches and 0.752 inches
Grip Diameter:
Between 0.4985 inches and 0.4995 inches
Thread Diameter:
0.500 inches
Grip Length:
Between 4.365 inches and 4.385 inches
Thready Qty Per Inch (tpi):
20
Min. Tensile Strength (psi):
160000 pounds per square inch
Hardness Rating:
36.0 rockwell c and 40.0 rockwell c
Surface Finish:
63.0 microinches grip
Material:
Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 8735 or steel comp 6150
Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:
Qq-p-416 ty2 cl3 federal specification single treatment response
Thread Series Designator:
Unjf
Specification Data:
80205-nas1308 professional/industrial association standard
Shelf Life:
N/a
Unit Of Measure:
-

--

NSN 5306-01-250-9658

Shear Bolt - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0