## NSN 5306-01-251-1970

Shear Bolt - Page 1 of 2

Between 0.400 inches and 0.450 inches

Between 0.660 inches and 0.690 inches

**Thread Class:** 

Right-hand

Thread Length:

**Thread Direction:** 

Fastener Length:

За



View Online at https://aerobasegroup.com/nsn/5306-01-251-1970

Head Style:								
Dished hexagon								
Head Height:								
Between 0.125 inches and 0.140 inches								
Width Between Flats:								
Between 0.430 inches and 0.439 inches								
Grip Diameter:								
Between 0.2485 inches and 0.2495 inches								
Thread Diameter:								
0.250 inches								
Grip Length:								
Between 0.240 inches and 0.260 inches								
Thready Qty Per Inch (tpi):								
28								
Min. Tensile Strength (psi):								
180000 pounds per square inch								
Hardness Rating:								
36.0 rockwell c and 40.0 rockwell c								
Surface Finish:								
32.0 microinches threads								
Material:								
Iron alloy 660								
Material Specification:								
Ams 5731 assn standard single material response								
Surface Treatment:								
Passivate								
Surface Treatment Specification:								
Qq-p-35 federal specification single treatment response								
Thread Series Designator:								
Unjf								
Specification Data:								
80205-nas1954 professional/industrial association standard								
Shelf Life:								
N/a								

## NSN 5306-01-251-1970

Shear Bolt - Page 2 of 2



			ıre:

--

Demilitarization:

No

Fiig:

A003b0