

View Online at <https://aerobasegroup.com/nsn/5306-01-251-9585>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.578 inches

Fastener Length:

Between 3.438 inches and 3.468 inches

Head Style:

Hexagon

Head Height:

Between 0.188 inches and 0.203 inches

Width Between Flats:

Between 0.554 inches and 0.564 inches

Hole Diameter:

Between 0.070 inches and 0.080 inches

Grip Diameter:

Between 0.3735 inches and 0.3745 inches

Thread Diameter:

0.3750 inches

Grip Length:

Between 2.865 inches and 2.885 inches

Thread Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

160000 pounds per square inch

Hole Configuration Style:

Hexagon corners

Material:

Steel comp 4340 or steel comp 8740

Material Specification:

Mil-s-5000 military specification 1st material response or mil-s-6049 military specification 1st material response or ams6322 assn standard 1st material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416a ty2 cl2 federal specification single treatment response

Thread Series Designator:

Unjf

Specification Data:

80205-nas6606 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5000 spec.