## NSN 5306-01-253-4126

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-253-4126
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.469 inches
Fastener Length:
Between 5.329 inches and 5.359 inches
Head Style:
Dished hexagon
Head Height:
Between 0.156 inches and 0.171 inches
Width Between Flats:
Between 0.492 inches and 0.502 inches
Hole Diameter:
Between 0.070 inches and 0.080 inches
Grip Diameter:
Between 0.3110 inches and 0.3120 inches
Thread Diameter:
0.3125 inches
Grip Length:
Between 4.865 inches and 4.885 inches
Thready Qty Per Inch (tpi):
24
Hole Configuration Style:
Hexagon corners
Material:
Steel comp 4340 or steel comp 8740
Material Specification:
Mil-s-5000 military specification 1st material response or mil-s-6049 military specification 2nd material response or ams6322 assn standard
2nd material response
Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:
Qq-p-416a, typ ii, cls 2 federal specification all treatment responses
Thread Series Designator:
Unjf
Specification Data:
80205-nas6605 professional/industrial association standard
Shelf Life:
N/a
Unit Of Measure:

--

## NSN 5306-01-253-4126

Shear Bolt - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5000 spec.