NSN 5306-01-253-4422

Machine Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-253-4422

View Crimite at https://acressacogreep.com/no.i/cooce C · 200 · 122
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.499 inches and 0.578 inches
Fastener Length:
Between 4.265 inches and 4.312 inches
Head Style:
Hexagon
Head Height:
Between 0.203 inches and 0.234 inches
Width Between Flats:
Between 0.430 inches and 0.439 inches
Hole Diameter:
Between 0.065 inches and 0.075 inches
Thread Diameter:
0.250 inches
Grip Length:
Between 3.734 inches and 3.766 inches
Hole Quantity:
3
Hole Type:
Drilled
Features Provided:
Finished head
Thready Qty Per Inch (tpi):
28
Min. Tensile Strength (psi):
125000 pounds per square inch
Hardness Rating:
26.0 rockwell c and 32.0 rockwell c
Hole Configuration Style:
Hexagon flats
Material:
Steel comp 4140 or steel comp 8740 or steel comp 8630 or steel comp 8735 or steel comp 4130 or steel comp 4037
Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:
Qq-p-416, type 2, class 3 federal specification single treatment response
Thread Series Designator:
Unf

NSN 5306-01-253-4422

Machine Bolt - Page 2 of 2



	Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0