NSN 5306-01-253-5913

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-253-5913

View Online at https://aerobasegroup.com/nsn/5306-01-253-5913
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.429 inches and 0.479 inches
Fastener Length:
Between 0.939 inches and 0.969 inches
Head Style:
Dished hexagon
Head Height:
Between 0.188 inches and 0.203 inches
Width Between Flats:
Between 0.554 inches and 0.564 inches
Grip Diameter:
Between 0.3735 inches and 0.3745 inches
Thread Diameter:
0.375 inches
Grip Length:
Between 0.490 inches and 0.510 inches
Thready Qty Per Inch (tpi):
24
Min. Tensile Strength (psi):
160000 pounds per square inch
Surface Finish:
32.0 microinches threads
Material:
Iron alloy 660
Material Specification:
Ams 5731 assn standard single material response or ams 5737 assn standard single material response
Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:
Qq-p-416, type 2 cl 2 federal specification single treatment response
Thread Series Designator:
Unjf
Specification Data:
Specification Data: 80205-nas6306 professional/industrial association standard
80205-nas6306 professional/industrial association standard
80205-nas6306 professional/industrial association standard Shelf Life:

--

NSN 5306-01-253-5913

Shear Bolt - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0