

View Online at <https://aerobasegroup.com/nsn/5306-01-253-7112>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.520 inches

**Fastener Length:**

2.314 inches

**Head Style:**

Round w/wrench flats

**Head Diameter:**

1.000 inches

**Head Height:**

0.120 inches

**Width Between Flats:**

0.870 inches

**Shoulder Diameter:**

0.748 inches first shoulder and 0.749 inches first shoulder

**Shoulder Length:**

1.784 inches first shoulder and 1.794 inches first shoulder

**Shank Unthreaded Hole Diameter:**

0.109 inches first hole

**Thread Diameter:**

0.625 inches

**Thready Qty Per Inch (tpi):**

18

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

2.156 inches first hole

**Shoulder Shape:**

Round first shoulder

**Special Features:**

Paint head white 17925, fed 595

**Material:**

Steel comp xm-13

**Material Specification:**

Ams 5629 assn standard single material response

**Surface Treatment:**

Enamel

**Surface Treatment Specification:**

Mil-p-23377 military specification single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-p-23377 spec.